

(19)

Europäisches Patentamt
European Patent Office
Office européen des brevets

"AR"



(11)

EP 0 969 567 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
05.01.2000 Bulletin 2000/01

(51) Int. Cl.⁷: H01R 13/658, H01R 13/41

(21) Application number: 99202033.9

(22) Date of filing: 24.06.1999

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 30.06.1998 NL 1009530

(71) Applicant:
FRAMATOME CONNECTORS INTERNATIONAL
92400 Courbevoie (FR)

(72) Inventors:
• Droesbeke, Gert
2560 Nijlen (BE)

• Van den Torren, Luc
2820 Bonheiden (BE)
• Van Koetsem, Jan Peter Karel
2070 Zwijndrecht (BE)
• Jonckheere, Luc
1700 Dilbeek (BE)

(74) Representative:
de Vries, Johannes Hendrik Fokke
De Vries & Metman,
Overschiestraat 184 N
1062 XK Amsterdam (NL)

(54) Connector

(57) A connector for high frequency signals comprises a housing of insulating material and a plurality of male contact elements. The housing has a bottom and two opposite side walls extending upwardly from the bottom, the bottom and side walls determining a receiving space. The bottom is provided with cavities regularly arranged in rows and columns. Each of the contact elements is mounted in a cavity, an upper end of each contact element projecting into the receiving space. At least a plurality of the cavities are metallized at their inner walls. The contact elements are mounted in the metallized cavities by means of a support element of insulating material. Each support has a lower extension directed away from the receiving space and each support element is metallized at its outer side.




fig.1

EP 0 969 567 A1

Description

[0001] The invention relates to a connector for high frequency signals, comprising a housing of insulating material and a plurality of male contact elements, said housing having a bottom and two opposite side walls extending upwardly from the bottom, the bottom and side walls determining a receiving space, wherein the bottom is provided with cavities regularly arranged in rows and columns, wherein each of the contact elements is mounted in a cavity, an upper end of each contact element projecting into the receiving space.

[0002] In a connector of the above-mentioned type it is known to use a number of the male contact elements as ground contact elements as a shielding for the signal contact elements. In this manner the number of contact elements which can be used as signal contact elements significantly decreases so that the signal density of the connector is relatively low.

[0003] The invention aims to provide a connector of the above-mentioned type with improved shielding and increased signal density, which connector can be adapted to different applications in an easy manner.

[0004] To this end the connector of the invention is characterized in that at least a plurality of the cavities are metallized at their inner walls, wherein the contact elements are mounted in the metallized cavities by means of a support element of insulating material, wherein each support element has a lower extension directed away from the receiving space, each support element being metallized at its outer side.

[0005] In this manner a connector is obtained, wherein all contact elements mounted in metallized cavities can be used as signal contact elements thereby increasing the signal density significantly. Further, the connector can be adapted to different applications by combining the housing with contact elements having a support element made in accordance with a given application.

[0006] The invention will be further explained by reference to the drawings in which an embodiment of the connector of the invention is schematically shown.

Fig. 1 shows a perspective view of an embodiment of the connector of the invention.

Fig. 2 shows detail II of fig. 1 at a larger scale.

Fig. 3 shows a contact element of the connector of fig. 1 at a larger scale.

Fig. 4 is a cross section of the connector of fig. 1 as mounted on a printed circuit board.

[0007] Fig. 1 shows a connector 1, in particular a connector for high frequency signals. The connector 1 comprises a housing 2 of insulating material and a number of male contact elements 3 arranged in rows and columns in a usual manner. For the sake of clarity only some of the contact elements 3 are shown in fig. 1. The housing is provided with a bottom 4 and two opposite side walls 5 extending upwardly from the bottom 4. The

bottom 4 and side walls 5 determine a receiving space 6 for receiving a female connector with female contact elements not further shown.

[0008] As can be seen in fig. 1, the bottom 4 is provided with cavities 7 for receiving the contact elements 3 and these cavities 7 are arranged in row and columns. The cavities 7 are metallized at their inner walls and the contact elements 3 are mounted in the cavities 7 by means of a support element 8 of insulating material. As shown in more detail in fig. 2 and 3, each support element comprises a body 9 having an outer dimension which is smaller than the inner dimension of the corresponding cavity 7. Further, the support element 8 comprises a plurality of ledges 10 extending mainly in axial direction of the contact element 3 and determining an outer dimension which is larger than the inner dimension of the corresponding cavity. In this manner a stable mounting and positioning of the contact elements 3 within the housing 2 is guaranteed.

[0009] Further the support elements 8 are provided at their upper side with a head part 11 for locking the contact elements 3 in the cavities 7. The inner wall of each metallized cavity 7 is provided with inwardly projecting ledges 12 at opposite sides and these ledges 12 engage into slots 13 at opposite sides of the head part 11. To facilitate mounting of the contact elements 3 in the cavities 7, the head part 11 is provided with oblique faces 14 extending outwardly and downwardly from the contact pin 3 towards said slots 13.

[0010] The support elements 8 are further provided with a lower extension 15 surrounding the contact element 3 and at the side opposite the receiving space 6 a further body 16 with ledges 17 is provided just as a further head part 18. The head part 18 is exactly the same as the head part 11. The complete support element 8 from the body 9 and ledges 10 up to the body 16 and ledges 17 is metallized so that the contact element 3 behaves as a coaxial contact element, the metallization being the outer conductor. The ledges 10 provide an interconnection between the metallization of the inner walls of the cavity 7 and the metallization of the support element 8.

[0011] The connector 1 described is suitable for mounting on a printed circuit board 19 having a slot 20 for receiving the extensions 15 of the support elements 8. At the side opposite of the housing 2 (lower side in fig. 4) a housing or shroud 21 can be mounted. The bottom of this housing is provided with cavities 7 in the same manner as the bottom 4 of the housing 2 to receive the head parts 18.

[0012] Both outer ends of the contact elements 3 are made as male contact pins for connection to female contact elements not shown.

[0013] At both sides of the cavities 7 standard cavities 22 are provided in which standard male contact elements 23 are mounted. As the complete housing 2 is metallized, these cavities 22 are also metallized at their inner walls and this metallization is contacted by the

contact elements 23. The contact elements 23 are provided with a press-fit sections 24. These press-fit sections 24 are inserted into plated through holes 25 of the printed circuit board 19. In this manner the connector 1 is mounted and fixed on the printed circuit board 19 and a ground connection with the printed circuit board 19 is thereby obtained.

[0014] The connector 1 described shows the advantage that the connector can be adapted to different applications in an easy manner. The same housing 2 can be used with different contact elements 3 with different support elements 8.

[0015] The support elements 8 are mounted on the contact elements 3 by overmoulding and a fixation of the support element 8 on the contact element 3 is obtained by providing the contact elements with projections, a thickening or the like.

[0016] The invention is not restricted to above described embodiment which can be varied in a number of ways within the scope of the claims.

Claims

1. Connector for high frequency signals, comprising a housing of insulating material and a plurality of male contact elements, said housing having a bottom and two opposite side walls extending upwardly from the bottom, the bottom and side walls determining a receiving space, wherein the bottom is provided with cavities regularly arranged in rows and columns, wherein each of the contact elements is mounted in a cavity, an upper end of each contact element projecting into the receiving space, characterized in that at least a plurality of the cavities are metallized at their the inner walls, wherein the contact elements are mounted in the metallized cavities by means of a support element of insulating material, wherein each support element has a lower extension directed away from the receiving space, each support element being metallized at its outer side.
2. Connector according to claim 1, wherein each support element comprises a body having an outer dimension which is smaller than the inner dimension of the corresponding cavity, and a plurality of ledges extending mainly in axial direction of the contact element and determining an outer dimension which is larger than the inner dimension of the corresponding cavity.
3. Connector according to claim 1 or 2, wherein the inner wall of each cavity and the support element of the corresponding contact element are provided with cooperating locking means for locking the contact element in the cavity.
4. Connector according to claim 3, wherein the inner wall of each metallized cavity is provided with two opposite protruding ledges and each corresponding support element is provided with a head part having slots at opposite sides for receiving the ledges.
5. Connector according to claim 4, wherein each support element is provided at both axial ends with a head part having slots at opposite sides for receiving the ledges of a cavity.
6. Connector according to claim 4 or 5, wherein the (each) head part is provided with oblique faces extending outwardly and downwardly (or upwardly, respectively) from the contact pin towards said slots.
7. Connector according to anyone of the preceding claims, wherein each support element is fixed to the corresponding contact element, preferably by overmoulding.
8. Connector according to anyone of the preceding claims, wherein the housing is completely metallized.
9. Connector according to anyone of the preceding claims, wherein a row of cavities is provided at each side of the rows of metallized cavities, wherein male ground contact elements are mounted in the cavities of these rows, said ground contact elements contacting the metallization in the corresponding cavities and having terminals for connection to a printed circuit board.
10. Connector according to claim 9, wherein said terminals of the ground contact elements are made as press-fit terminals.




fig.1

fig.2




fig. 3




fig.4



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 20 2033

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION
X	EP 0 693 795 A (CONNECTOR SYSTEMS TECH NV) 24 January 1996 (1996-01-24) * column 1 - column 8; figures 1-9 *	1	H01R13/658 H01R13/41
A	US 5 647 768 A (MESSURI DOMINIC ANTHONY ET AL) 15 July 1997 (1997-07-15) * column 2, line 9 - column 3; figures 1-4 *	1,8,10	
A	US 3 774 142 A (SIEGLER F) 20 November 1973 (1973-11-20) * column 2, line 31 - column 3, line 19; figures 1-3 *	9,10	
A	FR 2 693 845 A (AIR LB INTERNATIONAL SA) 21 January 1994 (1994-01-21) * page 1 - page 7; figures 1-4 *	3	
A	EP 0 809 331 A (BKS KABEL SERVICE AG) 26 November 1997 (1997-11-26) * column 3, line 4 - column 8, line 4; figures 1-10 *	1	
			TECHNICAL FIELDS SEARCHED
			H01R
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 26 July 1999	Examiner Tappeiner, R
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03/82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 20 2033

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

26-07-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0693795 A	24-01-1996	US 5743765 A	28-04-1998
		DE 69417224 D	22-04-1999
		JP 8288019 A	01-11-1998
US 5647768 A	15-07-1997	EP 0801444 A	15-10-1997
US 3774142 A	20-11-1973	AU 5474773 A	24-10-1974
		BE 799300 A	31-08-1973
		CA 977432 A	04-11-1975
		DE 2323739 A	29-11-1973
		DK 138380 B	21-08-1978
		FR 2184011 A	21-12-1973
		GB 1385664 A	26-02-1975
		IT 986298 B	20-01-1975
		JP 49054882 A	28-05-1974
		JP 55020638 B	04-06-1980
		NL 7306156 A	13-11-1973
FR 2693845 A	21-01-1994	NONE	
EP 0809331 A	26-11-1997	AT 181462 T	15-07-1999
		CA 2205723 A	23-11-1997
		DE 59602239 D	22-07-1999
		US 5895292 A	20-04-1999

EPO FORM P4439

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82